

LED Product Portfolio

Mid-power (0.2–1 W)

High-power (1–4 W)

Ultra-high-power (> 4 W)

Professional



OSCONIQ® S 3030
 – 0.2 W (3 V) 35–37 lm*
 – 1.0 W (6 V) 137–154 lm
 – CRI 70
 – CRI 80



OSCONIQ® P 2226 white
 – 37–42 lm
 – CRI 60
 – CRI 80



OSCONIQ® P 2226 color
 – Deep blue
 – Blue
 – True green
 – Yellow
 – Red
 – Hyper red
 – Far red



OSLON® SSL white
 – 160 lm
 – 80°, 150°
 – CRI 70
 – CRI 80
 – CRI 90



OSLON® SSL color
 – 80°, 120°, 150°
 – Deep blue
 – Blue
 – True green
 – Yellow
 – Amber
 – Red
 – Hyper red
 – Far red



OSLON® Square white
 – 340 lm
 – CRI 70
 – CRI 80
 – CRI 90



OSLON® Square color
 – Deep blue
 – Hyper red



OSCONIQ® P 3030 color
 – Deep blue
 – Blue
 – True green
 – Mint
 – Verde
 – PC Yellow
 – Amber
 – Red
 – Hyper red
 – Far red



OSLON® Pure 1010*
 – 100 lm
 – 120°
 – CRI 80/90



OSCONIQ® P 3030 white
 – 160 lm
 – 120°
 – CRI 70/80



OSCONIQ® P 3737
 – 2.0 W 320 lm
 – 3.0 W 490 lm
 – CRI 70/80/90



SOLERIQ® S 9
 – 700–2,000 lm
 – CRI 80/85/90/98
 – Brilliant White



SOLERIQ® S 13
 – 710–3,700 lm
 – CRI 70/80/85/90
 – Brilliant White
 – Brilliant Color



SOLERIQ® S 15
 – 2,500–4,000 lm
 – CRI 80/90




SOLERIQ® S 19
 – 2,500–7,900 lm
 – CRI 70/80/85/90
 – Brilliant White
 – Brilliant Color




OSCONIQ® P 7070
 – 1,185 lm
 – CRI 70/80


Consumer




DURIS® S 5 white
 – 0.2 W (3 V) 25–40 lm
 – 1.0 W (6 V) 102–153 lm
 – CRI 70/80/90




DURIS® S 5 color (3 V)
 – Deep blue
 – Blue
 – True Green
 – Amber
 – Red
 – PC Lime
 – PC Yellow
 – PC Purple
 – Full spectrum




DURIS® S 5 color (6 V)
 – Deep blue
 – PC Green
 – PC Amber
 – PC Red
 – PC Purple
 – Full spectrum




DURIS® E 3
 – 26–31.5 lm
 – CRI 70
 – CRI 80
 – CRI 90




DURIS® E 5
 – 30–56 lm
 – CRI 70
 – CRI 80
 – CRI 90




DURIS® E 2835
 – 0.2 W (3 V) 27–30 lm
 – 0.5 W (3 V) 55–67 lm
 – 1.0 W (9 V) 102–113 lm
 – CRI 80
 – CRI 90




DURIS® L 38
 – 80–250 lm
 – CRI 80
 – CRI 82




DURIS® T 49
 – Customizable filament design



DURIS® S 8
 – 350–580 lm
 – CRI 70
 – CRI 80
 – CRI 90



DURIS® S 8
 – 500–720 lm
 – CRI 70
 – CRI 80
 – CRI 90



DURIS® S 10
 – 850–1,730 lm
 – CRI 70
 – CRI 80
 – CRI 90

Reference CCT: 5,000 K @ CRI 80

Reference CCT: 5,000 K @ CRI 70

*Chip ARRAY SMD

Reference CCT: 3,000 K @ CRI 80, OSCONIQ® P 7070: 5,000 K @ CRI 70