#### **Technical Information**

No. DO 5109

Edition: 08/11 - subject to change

Supersedes 09/0 Status: valid

# Tungsten Halogen Lamp for Airfield Lighting

## 64317 IRC-C

#### Product description

The OSRAM 64317 IRC-C is a tungsten halogen lamp with 10% more light output as a standard 45W lamp and with triple lifetime. It is comparable to the 64319 IRC-A but with 16.0 mm instead of 20.0 mm LCL and is used for the following applications:

Taxiway centre line, stopbar, runway edge, taxiway edge, runway end, threshold and approach lighting.

mm

#### ■ Technical data

Order reference		64317 IRC-C 45-30	<b>└</b>
LIF		J1/76	11 11
Maximum operation current	Α	6.6	וֹוֹוֹ
Base		PK30d	
Connector	С	male <sup>1</sup>	
Cable length	mm	min. 125	
Rated lamp wattage	W	45	
Maximum initial wattage	W	48,5	·
Average life	h	3,000	
Color temperature	K	3,000	·
Rated luminous flux	lm	800	
Minimum initial luminous flux	lm	730	
Luminous flux after 2,250 h	lm	min. 90% of initial value	
Bulb diameter (d)	mm	max. 15	
Length (I <sub>1</sub> )	mm	max. 28	
Length (I <sub>2</sub> )	mm	max. 20	
LCL (a)	mm	16.0	
Filament type		C-8	•
Filament dimensions (w x h)	mm	2.1 x 2.9	

### Lamp operation

Deviation of filament centre

Burning position		s 90
Maximum pinch temperature	°C	350
Chromaticity		within white boundaries as defined in Annex 14 to the Convention of International Civil Aviation

max. 1.0 (refers to base axis)



<sup>&</sup>lt;sup>1</sup> Male connector C complies with DIN 46248